

*I'D Selbstbremsendes Abseil- und Sicherungsgerät /
I'D Self-breaking descender and safety device*
euroline®



Zum Abseilen und zum Sichern.

Verfügt über ein Anti-Panik-System. Das Seil läßt sich dank des drehbaren Seitenteils mit Clip rasch in das Gerät einlegen, ohne dies vom Gurt lösen zu müssen

Verbesserte Sicherheit:

- Anti-Fehler-Funktion, um Unfälle durch falsches Einlegen des Seils zu verhindern
- Automatisches Blockiersystem: Mechanisches System mit drehbarem Klemmnocken, der das Seil abklemmt und blockiert, falls der Benutzer den Hebel des Geräts losläßt
- Anti-Panik-Hebel: Das I'D blockiert wenn der Benutzer zu stark am Hebel zieht
- Bequeme Handhabung: Zum Abseilen ziehen Sie einfach am Hebel. Die Steuerung des Seildurchlaufs erfolgt, indem das freie Seilende mit der anderen Hand mehr oder weniger fest umschlossen wird
- Der Aufstieg am Seil ist möglich ohne die Position des Gerätes zu ändern. Fügen Sie einfach eine Trittschlinge und eine Seilklemme mit Griff hinzu
- Kann zum Sichern im Vorstieg und Nachstieg verwendet werden
- Extrem solide und abnutzungsfest. Der Körper ist aus eloxiertem Aluminium und rostfreiem Stahl gefertigt, der Hebel zum Lösen des Seils aus glasfaserverstärktem Polyamid

Gewicht: 530 g

Best. Nr. 4290017

Zulassung: EN 341 Klasse A

For abseiling and protection.

Is provided with an anti-panic system. The rope can be inserted quickly into the device thanks to the revolving side part with clip, without needing to detach it from the belt

Better safety:

- Anti-fault function, in order to avoid accidents due to wrong insertion of the rope
- Automatic blocking system: Mechanical system with a revolving clamp cam that clamps the rope and blocks it if the user releases the lever of the device
- Anti-panic lever: The I'D blocks if the user pulls the lever too much
- Comfortable handling: For abseiling simply pull the lever. The rope run is controlled by grasping more or less firmly the free end of the rope with the other hand.
- Ascent on the rope is possible without changing the position of the device. Simply add a step loop and a rope clamp with handle
- Can be used to protect the leading climber and the following climber
- Extremely solid and resisting wear. The body is made of anodized aluminium and stainless steel, the lever to loosen the rope of glass fibre reinforced polyamide

Weight: 530 g

Art. No. 4290017

Approval: EN 341 Class A